



Zebra® GT800™

Desktop Printer

FLEXIBLE, VERSATILE, EASY TO USE

Providing performance features at a competitive price, the GT800 thermal transfer/ direct thermal desktop printer offers a wide range of advanced functionality to meet a variety of low- to medium-volume printing applications.

The GT800 printer supports both 300 Meter and 74 Meter ribbon capacities — without the need to change settings for different ribbon lengths. Users easily select the appropriate length for the task at hand.

The intuitive design of the GT800 printer combines a choice of three connectivity interfaces and optional 10/100 Ethernet, co-resident EPL2™ and ZPL II® programming languages, Unicode™ and optional ZBI 2.0™ to ensure quick and efficient integration.

Print labels even faster with the printer's powerful 32-bit processor and its large memory for quicker processing and support for more graphics and longer labels. Designed to save you time and money on ongoing printer management and operator intervention, the printer features status reporting, odometer control and increased ribbon capacity.

With a durable, compact design, the GT800 is equipped with a standard moveable sensor to handle a greater range of custom and Genuine Zebra™ supplies and ensure consistent registration. Enhanced media handling options include the full-width cutter or peel dispenser options.

With print speeds up to 5 inches per second (ips), the GT800 offers users a choice of 203 or 300 dots per inch (dpi) resolution for applications requiring finer, high-quality output.

The larger ribbon capacity and ease of use make the compact GT800 desktop printer an ideal, affordable choice.

For more information, visit www.zebra.com/GT800.

Ideal for these applications:

Manufacturing

- Light-industrial work-in-process
- Product and shipping labeling

Transportation & Logistics

- Boarding tickets
- Bag tags
- Parking passes

Government

- Asset management
- Documents management
- Evidence tracking

Healthcare

- Laboratory specimen
- Blood bank labeling

Retail

- Price labeling
- Receipt printing

Specifications Chart*

PRINTER NAME		OPERATING CHARACTERISTICS		COMMUNICATION AND INTERFACE CAPABILITIES	
GT800 (not available in North America)		Operating Temperature 40~105°F/ 4.4~41°C		- Centronics® Parallel (36pin) connector ports - RS-232 Serial interface - USB V1.1 interface, bi-directional - Optional Ethernet: 10/100 internal (replaces Parallel port)	
STANDARD FEATURES		Storage Temperature -40~140°F/ -40~60°C		ZEBRALINK™ SOLUTIONS	
300 meter ribbon capacity 32 bit RISC processor - Co-resident EPL and ZPL II programming languages - Triple connectivity: Serial, USB and Parallel - Print methods: Thermal transfer and direct thermal modes - Construction: Dual-wall frame, reinforced plastic - OpenACCESS™ for easy media and ribbon loading - Certified Microsoft® Windows® drivers - ENERGY STAR® qualified		Operating Humidity 10% ~ 90% non-condensing		Software ZebraDesigner Pro: An intuitive, easy-to-use software program for creating complex label designs (optional) ZebraDesigner: Offers basic features for simple label design (standard) ZebraNet™ Bridge Enterprise: Centrally manage Zebra printers anywhere on your global network from a single PC screen (optional) ZebraNet Utilities v 7.0: Provides printer administration, management, alerting capabilities and more for Windows® 95/98/2000/2003/ME/NT/XP (standard) ZebraDesigner™ Windows Driver: Microsoft certified for Windows Vista®, Windows 7, Windows 8 Windows 8.1, Windows 2008, and Windows 2012 (downloadable from www.Zebra.com) ZBI 2.0: Powerful programming language that lets printers run standalone applications, connect to peripherals and much more (optional) ZBI-Developer: Programming environment for developers to simplify creation, testing and distribution to printers of complex ZBI 2.0 programs (standard with ZBI 2.0)	
PRINTER SPECIFICATIONS		Storage Humidity 5% ~ 95% non-condensing		Firmware ZBI 2.0™: Powerful programming language that lets printers run stand-alone applications, connect to peripherals, and much more (option) ZBI-Developer™: Programming utility makes it dramatically easier for programmers to create and test complex ZBI 2.0 programs and distribute them to the printer (standard with ZBI 2.0) ZPL II®: Zebra Programming Language provides sophisticated label formatting and printer control and is compatible with tabletop and mobile Zebra printers EPL2™: Eltron Programming Language simplifies label formatting and enables format compatibility with legacy applications	
Resolution 203dpi/ 8dots per mm (standard) 300dpi/ 12dots per mm (optional)		FONTS/ GRAPHICS/ SYMBOLOGIES			
Memory 8MB Flash, 8MB SDRAM		16 resident expandable ZPL fonts - One resident scalable ZPL font 5 resident expandable EPL2 fonts - Supports user-defined fonts and graphics — including custom logos			
Print Width 4.09" 104mm		BAR CODE SYMBOLOGIES			
Print Length 39" 991mm		LineBar Code Ratios 2:1 (non-rotated) and 3:1			
Print Speed 5"/ 127mm per second (203dpi) 4"/ 102mm per second (300dpi)		Linear Bar Codes Codabar, Code 11 (ZPL), Code 128, Code 39, Code 93, Code 93, EAN-13, EAN-8, EAN-14 (ZPL), German Post Code (EPL), Industrial 2-of-5 (ZPL), Interleaved 2-of-5, Japanese Postnet (EPL), ISBT-128 (ZPL), Logmars (ZPL), MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5 (ZPL), UCC/EAN-128 (EPL), UPC and EAN 2 or 5 digit extensions (ZPL), UPC-A, UPC-A and UPC-E with EAN 2 or 5 digit extensions, UPC-E, and GS1 Databar (formerly RSS)			
Media Sensors Multi-position transmissive and full-width reflective sensor		2-Dimensional Codablock (ZPL), Code 49 (ZPL), Data Matrix, MaxiCode, QR Code, PDF417, MicroPDF417, Aztec (For EPL and ZPL except where noted)			
MEDIA CHARACTERISTICS		OPTIONS AND ACCESSORIES			
Media Width 0.75~4.49" / 19.05~114mm		300dpi/ 12 dots per mm - Dispenser: Label peel and present with label present sensor - Full-width cutter - ZebraNet 10/100 Print Server: Internal Ethernet for network communication and printing - ZKDU™ and KDU Plus™: Keyboard display units for stand-alone printing solutions			
Media Length 0.25~39" / 6.35~991mm					
Maximum Media Roll Size 5" / 127mm O.D. on a 1" / 25.4mm, 1.5" / 38mm I.D. core					
Media Thickness 0.003~0.007" / 0.08~0.18mm					
Media Types Roll-fed or fan-fed, die cut or continuous direct thermal labels with or without black mark, tag stock, continuous receipt paper, wristbands, and optional liner-free direct thermal media					
PHYSICAL CHARACTERISTICS					
Width 7.75" / 197mm					
Height 7.25" / 184mm					
Depth 10.75" / 273mm					
Weight 5.8 lbs/ 2.63kg					
RIBBON CHARACTERISTICS					
Outside Diameter 2.6" / 66mm (300m); 1.34" / 34mm (74m)					
Standard Length 984' (300m); 244' (74m)					
Ratio 1:4 media to ribbon (300m) 1:1 media to ribbon (74m)					
Width 1.33~4.3" / 33.8~109.2mm					
Core I.D. 300 Meter ribbon 1" / 25.4mm 74 Meter ribbon 0.5" / 12.7mm					



Asia-Pacific Headquarters | +65 6858 0722 | contact.apac@zebra.com

*Specifications subject to change without notice. ©2016 ZIH Corp. All rights reserved. All product names and numbers are Zebra trademarks, and Zebra, the Zebra head graphic, ZPL, ZPL II and ZebraNet are registered trademarks of ZIH Corp.. All rights reserved. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Centronics is a registered trademark of Centronics Data Computer Corporation. ENERGY STAR and the ENERGY STAR mark are registered marks owned by the U.S. government. All other trademarks are the property of their respective owners. 05/2016 (AP)